

TADA : F.R.L Combination (Airtac Style)

AR, BR Series Regulator

AFR, BFR Series Filter & Regulator



Ordering Code

BR

Type
 AR : Small Size
 BR : Middle Size
 AFR : Small Size
 BFR : Middle Size

2000


Joint Pipe Bore
 2000 : G1/4"
 3000 : G3/8"
 4000 : G1/2"

D


Drain Type
 Blank : Differential Drain
 D : Automatic Drain

Graphic Symbol

AFR & BFR



AR & BR



Specification

Model	AR1500	AR2000	BR2000	BR3000	BR4000
	AFR1500	AFR2000	BFR2000	BFR3000	BFR4000
Operatin Fluid	Air				
Joint Pipe Bore	G1/8"	G1/4"	G1/4"	G3/8"	G1/2"
Range Of Adjustable Pressure	0.05~0.85 Mpa				
MAX.Adjustable Pressure	0.95 Mpa				
Ensured Pressure Resistance	1.5 Mpa				
Operating Temperature Range	5~60C				
Material body	Body	Aluminum Die - Casting Forming			
	Container Cup	PE			
	Protective Cup Cover	Iron			
Model	AR1500	AR2000	BR2000	BR3000	BR4000
	0.20 KG		0.23 KG		
Model	AFR1500	AFR2000	BFR2000	BFR3000	BFR4000
	0.26 KG		0.4 KG		